

A Cost Efficient Approach to Rigless P&A for Future Projects

Amalie Frafjord Andersen & Sara Marlen Kolstø

Agenda

01

Who we are

02

Scope of thesis & rigless P&A

03

Cases

04

Cost analysis

05

Result & Conclusion

Who Are We?

- Amalie Frafjord Andersen & Sara Marlen Kolstø
- Graduated from UiS in 2025 with a Master degree in Industrial Economy
- Graduates in Aker BP




Scope of Thesis

To what extent can rigless technologies offer a safer, cost-efficient, and lower-emission approach to P&A of platform wells in compliance with regulatory requirements?

- Cases:
 - Base Case: Conventional Drilling Rig (XLE jack-up rig)
 - Case 1: Modular Drilling Rigs (MDR)
 - Case 2: New rigless technologies
- Methodology:
 - Monte Carlo simulations for cost and time (Base Case & Cases 1 & 2)

PS: This Master Thesis is submitted to the University in Stavanger under supervision from Aker BP.

What is Rigless P&A?



Modular Drilling Rig



Flexible interventions



Cost-effective



Environmental
Perspective


- In this study, rigless P&A is defined as a set of technologies that enable well abandonment without the use of conventional drilling rigs

Cases


- P&A Phase 2

CASE	APPROACH	TECHNOLOGY USED	OPERATIONAL STEPS
Base Case	Rig-based	XLE rig	Full rig-based P&A with drill pipe operations
Case 1: MDR	Rigless	Modular Drilling Rig	Full abandonment with MDR including cutting, plugging, and barrier verification
Case 2: New Technology	Rigless	Wireline, Dual Logging, Axter System, dSolve, Bismuth, MDR	Dual logging, barrier installation through tubing using a wireline, then MDR

The Well Design Used for All the Cases





P&A phase 1: Before permanent P&A




P&A phase 2: Permanent P&A

Base Case: Procedure



Case 1: Modular drilling Rig (MDR)


- What is an MDR?
- Four fundamental functions:
 1. Tubing pulling operations
 2. Structural support for vertical operations
 3. Automated tubular handling and hoisting
 4. Circulation and pressure control systems



Illustrating an MDR from Odfjell Technology

Case 1: Procedure


- Perform the same steps as Base Case
- Challenge: Slower
- Advantage: Lower daily operational cost
- More economical?



Case 2: New Rigless Technologies

- Case 2A:

Epilogue: Dual Logging




Axter Retrieve



dSolve



wel-lok™ Tubing Seal





- Case 2B:

RockSolid




Case 2A: Procedure

- Reservoir Barrier:
 - Dual Logging
 - Remove control lines with Axter System
 - DSolve tool dissolve specific sections of tubing
 - Bismuth Plug
- Upper Barrier & Environmental plug:
 - MDR



Case 2B: Procedure

- Reservoir Barrier
 - RockSolid
 - Thermite-based exothermic reaction
 - Expand from within the tubing through the 9 5/8" casing
- Upper Barrier & Environmental plug:
 - MDR





Cost Analysis – Input

- Methodology
 - Monte Carlo simulation
- Data Collection
 - Time
 - Tripping, racking, POOH
 - Costs
 - Daily operational cost of XLE rig, MDR and wireline
 - Confidential, uses % as cost relative to base case
- Input data provided by Aker BP and vendors

Phase/Event Name	Distribution Type	Variable Unit
Skid rig and N/U on well		
Skid rig	Pert	Hours
Secure rig and prepare slot	Pert	Hours
Land HP and BOP riser on well	Pert	Hours
Land Bell nipple and diverter	Pert	Hours
Fill riser	Pert	Hours
Perform a connector test	Pert	Hours
Recover production tubing		
Pre job meeting	Spike	Hours
M/U Spear BHA	Pert	Hours
Engage Spear	Pert	Hours
Cycle open shallow e-Red valves	Pert	Hours
Pull TH free	Uniform	Hours
Circulate and condition mud	Pert	Hours
Flow check	Spike	Hours
POOH	Pert	<u>Trip</u> (Mt/Hr)
L/D Spear BHA	Pert	Hours
R/U casing equipment	Pert	Hours
Continue to pull and R/B tubing	Pert	<u>Trip</u> (Mt/Hr)
R/D casing handling equipment	Pert	Hours
Clean and clear rig floor	Spike	Hours
Clean out 9 5/8" csg		
Pre job meeting	Spike	Hours
M/U Cleanout BHA	Pert	Hours
RIH to tubing stump	Pert	<u>Trip</u> (Mt/Hr)
Clean well	Pert	Hours
Flow check	Spike	Hours
POOH w/BHA and log	Pert	<u>Trip</u> (Mt/Hr)
L/D Cleanout BHA	Spike	Hours
Clean and clear rig floor	Spike	Hours
Primary barrier - Set 9 5/8" EZSV and balanced cement		
Pre job meeting	Spike	Hours
MU EZSV	Pert	Hours
RIH with EZSV	Pert	<u>Trip</u> (Mt/Hr)
Set, tag and test EZSV	Pert	Hours
Set balanced cement plug	Pert	Hours
Pull to TOC and circulate	Pert	Hours
POOH	Pert	<u>Trip</u> (Mt/Hr)
LD EZSV RT	Pert	Hours
Clean and clear rig floor	Spike	Hours
Cut 9 5/8" casing		
Pre job meeting	Spike	Hours
M/U cut BHA	Pert	Hours
RIH	Pert	<u>Trip</u> (Mt/Hr)
Circulate to condition mud	Pert	Hours
Cut 9 5/8" casing below 18 5/8" casing shoe	Pert	Hours
Circulate behind 9 5/8" casing	Pert	Hours
POOH with cut assemblies	Pert	<u>Trip</u> (Mt/Hr)
LD cut assemblies	Pert	Hours
Recover 9 5/8" casing		

Output From The Simulation


Base case



Results: Overview

DISCLAIMER: This is a static review of single well assuming technology readiness and is not including platform specific costs, tool run charges for new technology and other limitations (see next slide)

Case		Mean P&A Phase 2 Duration (days)	Mean Cost (% compared to Base Case)
Base XLE	Case:	7,32	100 %
Case 1: MDR		10,93 (↑3,61)	57% (↓43%)
Case 2A: Axter, dSolve, Bismuth		12,45 (↑5,13)	56% (↓44%)
Case 2B: RockSolid		6,07 (↓1,25)	31% (↓69%)



Break- even cost:
$$RigCost_{MDR} = \frac{RigCost_{XLE} \cdot OperationTime_{XLE}}{OperationTime_{MDR}} = \frac{1 \cdot 7.32 \text{ days}}{10.93 \text{ days}} = 0.67$$

Limitations & Indirect Costs



Charges for new technology

- Tool run charges
- Investments



Platform specific costs

- Conditions of platform
- Number of wells
- Platform utilities
- Deck space
- Crane conditions



Operational Risks

- High Risk Scenarios
- Multiple SOIs
- Well conditions deviating from ideal case in this presentation



Logistical challenges

- Crew Capacity
- WOW/NPT

Conclusion



Simulations indicate that rigless technologies perform P&A operations at lower cost compared to conventional drilling rigs



Compared to Base Case:

Case 1 had 43 % lower cost
Case 2A had 44 % lower cost
Case 2B had 69 % lower cost

DISCLAIMER: This is a static review of single well assuming technology readiness and is not including platform specific costs, tool run charges for new technology and other limitations.



The cost estimates does not include the expenses associated with new technologies
→ represent the maximum investment one could make while remaining more cost-effective than a conventional rig-based approach

